

# Potmolen Paint



Traditional & Natural Paints

INFORMATION SHEET NR.050

## WATER THINNABLE TRADITIONAL & NATURAL COATINGS.

ALL COATINGS LISTED ARE MICROPOROUS BUT VARY IN DEGREE OF BREATHABILITY

### GENUINE DISTEMPERS

#### DISTEMPER SUPER

Water thinnable non-toxic distemper wall paint for interior use of superior trade quality, based on starch and cellulose derivatives. Wipeable (non washable) with excellent obliterating power and having a high degree of aqueous permeability. Easy to apply and has a neutral paint odour, therefore rooms can immediately be used after coating.

A standard distemper often referred to as soft distemper by many people

Spreading rate (practical): Approx. 11 m<sup>2</sup> per litre.

Packaging: 10 litre. (Paste) Colour range: White and light colours.

#### HOLLINS DISTEMPER

The Sovereign of Distempers, affectionately known as "Walop". Water thinnable non-toxic distemper wall paint for exterior & interior use of superior trade quality, based on pure natural oil convertible binder and resins dispersed in water. Scrubable with excellent obliterating power and adhesion. Easy to apply and has an agreeable traditional paint odour together with a high degree of aqueous permeability and fire retarding properties. Makes an excellent base for glazing and colour work. Makes an ideal spatchel (grain) filler on many surfaces.

Spreading rate (practical): Approx. 10 m<sup>2</sup> per litre.

Packaging: 5 litre. (Paste) Colour range: White and light colours.

#### AMSTEL DISTEMPER

High quality nature friendly non-toxic, abrasive resistant, serviceable wall paint for interior use of superior trade quality, based on pure natural oils and resins dispersed in water. Washable with excellent obliterating power and adhesion. Easy to apply and has an agreeable traditional paint odour together with a high degree of aqueous permeability.

Amstel Distemper may be used over sound emulsion coatings in buildings constructed after 1945.

Spreading rate (practical): Approx. 8 m<sup>2</sup> per litre.

Packaging: 5 litre. (Paste) Colour range: White and light colours.

INFORMATION SHEET NR.004 "WHAT WE MEAN BY DISTEMPER" IS NOW INCORPORATED IN OUR COLOUR BROCHURE.

The hand made products above are all natural and whilst SUPPLIED AS A PASTE ready for use (you only need to add water & stir) the viscosity may vary from tub to tub due to factors (heat, etc.) beyond our control, as is the case with all natural products.

People with allergies which are created or aggravated by late 20th century pollution very often find that our Distempers are a more acceptable alternative to synthetic wall coatings.

### OTHER WATER THINNABLE COATINGS

#### CHAPEL COAT

Water thinnable non-toxic lime wall coating for exterior & interior use, based on pure lime putty. Washable with excellent obliterating power. Easy to apply and has an agreeable traditional coating odour together with a high degree of aqueous permeability and fire retarding properties. Makes an ideal spatchel filler on many porous surfaces and may be used as a ready mixed skim coat in lime plasterwork.

Spreading rate (practical): Approx. 5 to 10 m<sup>2</sup> per litre. (SPECIAL ORDER ONLY)

Packaging: 10 litre. Colour range: White and light colours.

(Page One of Two)

27 WOODCOCK INDUSTRIAL ESTATE, WARMINSTER, WILTSHIRE GB-BA12 9DX

TELEPHONE: WARMINSTER (01985) 213960. (International +441985 213960)

TELEFAX: 0 19 85 21 39 31 (International +44 19 85 21 39 31)

Proprietor: The Potmolen Paint Company / Gillian R. Butcher

VAT Registration No. GB 712 8305 57

### **LIMEWASH**

The most durable and ancient coating for exterior and interior use made from our EXTRA FINE MATURE LIME PUTTY by just adding water. [Full instructions, Information Sheet NR.005, "MAKING LIMEWASH FROM EXTRA FINE MATURE LIME PUTTY" supplied with Lime Putty purchases].

10 litres Lime Putty makes 100 litres Limewash.

Spreading rate (practical): Approx.  $6\text{m}^2$  per litre. **LIMEWASH**

Packaging: 12.5 kilo (10 litre). **LIME PUTTY** Colour range: White & light colours.

### **TEMPERA COLOUR (PIGMENT WASH)**

Water thinnable non-toxic pigment paint for interior use, based on natural resin dispersion. Non Wipeable with excellent obliterating power and having a high degree of aqueous permeability. Highly concentrated colours which dry to a perfectly uniform and matt finish within a few minutes. Neutral smell. Our current replacement for Taleta; see note below.

Spreading rate (practical): Approx.  $40\text{m}^2$  per litre. 50ml covers  $2\text{m}^2$

Packaging: 50ml (250ml limit colours). Colour range: 27 Traditional pigment colours.

### **SCUMBLE GLAZE**

High quality nature friendly non-toxic, scumble glaze & glazing medium for interior use, based on pure natural oils and resins dispersed in water. For use as an interior colour wash and glaze finish for walls, etc.. Colourless and washable with excellent adhesion yet having aqueous permeability. Easy to apply and has an agreeable traditional paint odour. Thinning from 1:1 to 1:9 (glaze:water)

Spreading rate (practical): Approx. 8 to  $10\text{m}^2$  per litre.

Packaging: 0.75 & 2.5 litre. Colour range: Colourless

### **LINSTAIN EXTERIOR & LINSTAIN INTERIOR**

Unique high quality non-toxic, microporous, water thinnable translucent timber finish for exterior use, based on pure natural oils and resins dispersed in water. Easy to apply and has an agreeable traditional coating odour. The natural oil soaks into the wood, nourishes it naturally and protects it against the weather whilst the vegetable & bees waxes accentuate the natural aspect of the wood.

Spreading rate (practical): Approx. 8 to  $10\text{m}^2$  per litre.

Packaging: 0.75 litre. Colour range: Colourless & 4 timber colours

### **EXTRA FINE MATURE LIME PUTTY (WHITE RHINO)**

User friendly, self healing, Lime mortar/render/plaster is made with Lime Putty by the simple process of adding sand. Guaranteed at least 12 weeks old, often much older and SAFER to use THAN Ordinary Portland Cement. [Full instructions, Information Sheet NR.014 "LIME MORTAR, PLASTER & LATH MADE WITH EXTRA FINE MATURE LIME PUTTY" supplied with Lime Putty purchases].

Packaging: 12.5 kilos (makes 30 litres Lime mortar 1:3 mix) & 25 kg. [1000 lt. =  $\text{m}^3$ ]

### **PIGMENT WASH (TALETA)**

Water thinnable non-toxic pigment paint for interior use, based on synthetic resin dispersion. Wipeable (non washable) with excellent obliterating power and having a high degree of aqueous permeability. Highly concentrated colours which dry to a perfectly uniform and matt finish within a few minutes and will not crack on flexible grounds. Neutral smell.

Spreading rate (practical): Approx.  $40\text{m}^2$  per litre. 50ml covers  $2\text{m}^2$

Packaging: 50ml (750ml limit colours). Colour range: was 30 Traditional colours.

Some colours now only available in Tempera Colour.

### **PIGMENT WASH GENERAL**

Due to the demise of a top quality pigment manufacturer, we are at present reassessing our entire range. Further information will be issued when available.

TRADE PAINT = Professional Trade Paints as used by Guild Painters in Germany & The Netherlands.

FULL DATA SHEETS FOR OUR PRODUCTS ARE AVAILABLE ON REQUEST.

FULL DATA SHEETS ARE ALWAYS DISPATCHED WITH THE GOODS FROM OUR WORKS.

PLEASE READ FULL PRODUCT DATA SHEET & CONDITIONS BEFORE USING ANY PRODUCT.

THE HAND MADE NATURAL PRODUCTS ABOVE ARE SUPPLIED READY FOR USE, THE VISCOSITY HOWEVER MAY VARY FROM CAN TO CAN DUE TO FACTORS BEYOND OUR CONTROL, AS IS THE CASE WITH ALL NATURAL PRODUCTS.